


NOTE 1:
Rigid Air Barrier (RAB) also required in *Extra High* wind zones. Refer to E2/AS1 (section 9.1.7.2)

NOTE 2:
Detail depicts use of starter strip to locate a full board. Refer to NW-HOC-020 where a notched board occurs



Stop-end tabbed up on both sides of head flashing

General note:
• Cladding fixings omitted for clarity

Window setting out notes:
• 17-18mm for hollow fin windows
• 18-20mm for solid fin windows

Cavity batten note:
• 20mm timber battens required for all Nu-Wall horizontal board installations
• Batten to have 15° slope for moisture egress
• Battens to all internal, external corners, jambs, and sills to be sized to 18mm to accommodate flashing build up
• 20 and 18mm single castellated battens are available directly from Nu Wall
• Proprietary Nu-Wall AliBat is available as an alternative when a structural non-combustible batten is required



	Nu-Wall cladding horizontal on cavity Typical head section - full board using NC101 starter		NW-HOC-017.02	
	© 2021 copyright in this document is the property of Nu-Wall Aluminium Cladding Limited. All rights reserved. Nu-Wall is a registered trademark of Aluminium Product Brands NZ Limited	Drawn by: Nu-Wall	Date: 19/9/2024	Checked by: RL, GT